



# OR -1604C


Eco Solvent Printer (With Four I3200-E1 Heads) 8 Colors Printing



ORIC ECO INK



Four I3200-E1 Heads



\* 1.6m Four I3200-E1 Print Heads Speed (8 Colors)


720x1200dpi - 4pass	40 m <sup>2</sup> /h
720x1800dpi - 6pass	30 m <sup>2</sup> /h
720x2400dpi - 8pass	21 m <sup>2</sup> /h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subwayadvertising, shopping mall advertising signs




### ● Technical Specifications


<b>Model</b>	<b>OR-1604C</b>
Print Head	Four I3200-E1 Print Heads
Printing Technology	Piezoelectric Inkjet
Acceptable Media	Width 210-1650 (mm)
	Thickness Maximum 59 mil(1.5 mm)
	Weight 132 lb.(60 kg)
Printing Width	210-1600 (mm)
Ink Cartridges	Type Eco Solvent Ink
	Capacity Continual Ink Supply System ( 3L ink tank)
	Color C M Y K / C M Y K Lc Lm Lk LLk(4/8 Colors Optional)
Printing Resolution	Maximum 2400 dpi
Printing Speed	4pass(720x1200dpi) : 40 sqm/h(8 Colors)
	6pass(720x1800dpi) : 30 sqm/h(8 Colors)
	8pass(720x2400dpi) : 21 sqm/h(8 Colors)
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system
Interface	Ethernet Interface
Power	7500W
Power Supply	AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)	2675(W)*775(D)*650(H)(mm)
Weight(with stand)	
Package Dimensions	2920(W)*760(D)*100(H)(mm)
Package Weight	
Environment	Power on Temperature: 59°F to 90°F [15°C to 32°C] / Humidity: 35 to 80% (no condensation)
	Power off Temperature: 41°F to 104°F [5°C to 40°C] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridge, RIP software etc.




Printer carriage can be moved up and down to adjust print head height



Head cleaning and moisturizing makes operation and maintenance more convenient



High quality DC servo motor has good stability and long service life



Three-foot pinch roller structure brings more stable feeding accuracy



Stable 3L bulk system ensures amazing printing speed



Built-in infrared heater and cooling fan to accelerate the drying of the media



Three stage heating system including pre-heater, print heater, and rear heater and platform vacuum system with adjustable



External power supply, intelligent rolling